

Amendments to the Claims

This listing of the claims replaces all prior versions and listing of the claims in the present application.

Listing of the Claims

1. (canceled)
2. (currently amended) A GMPLS controller comprising:  
a plurality of switch controllers controlling a plurality of switch devices, respectively, each of said plurality of switch devices including at least one port;  
~~a port information table describing an association of said ports to a location of each of~~ said plurality of switch controllers; and  
a resource manager responsive to a label request indicative of a target port selected out of said ports for managing labels, and for issuing a device setup request,  
wherein said resource manager consults said port information table to ~~determine select~~ a target switch controller associated with said target port out of said plurality of switch controllers ~~using the locations of said plurality of switch controllers described in the port information table,~~ and provides said device setup request for said target switch controller, and  
wherein said target switch controller updates a setup of said switch device associated with said target switch controller.

3. (original) The GMPLS controller according to claim 2,  
further comprising:

a label database describing whether each of said labels is  
in use or not,

wherein said label request is indicative of a target label,  
and

wherein said resource manager updates said label database to  
indicate that said target label is in use.

4. (original) The GMPLS controller according to claim 2,  
further comprising:

at least one port-to-port connection controller for  
achieving a port-to-port connection between two out of said  
plurality of switch devices,

wherein said port information table describes an association  
of said ports to said at least one port-to-port connection  
controller,

wherein said resource manager is responsive to a port-to-  
port connection request indicative of another target port  
selected out of said ports for managing said labels, and for  
issuing another device setup request,

wherein said resource manager consults said port information  
table to determine a target port-to-port connection controller  
associated with said another target port out of at least one  
port-to-port connection controller, and provides said another

device setup request for said target port-to-port connection controller.

5. (original) The GMPLS controller according to claim 2, wherein said plurality of switch controllers include interfaces, respectively, and said interfaces use the same protocol to receive said device setup request.

6. (original) The GMPLS controller according to claim 2, wherein said plurality of switch devices include at least two out of an MPLS switch, a TDM switch, a Lambda switch, and a fiber switch.

7. (original) The GMPLS controller according to claim 2, wherein said resource manager manages bandwidth information of said GMPLS network.

8. (original) The GMPLS controller according to claim 2, wherein said resource manager manages LSP information of said GMPLS network.

9-13. (canceled)

14. (currently amended) A method for controlling switch devices provided for a GMPLS network, comprising:

providing a GMPLS controller including:

a plurality of switch controllers controlling a plurality of switch devices, respectively, each of said plurality of switch devices including at least one port;

a port information table describing a location of each  
of an association of said ports to said plurality of switch  
controllers;

providing a label request indicative of a target port  
selected out of said ports;

consulting said port information table to select determine a  
target switch controller associated with said target port out of  
said plurality of switch controllers using the locations of said  
plurality of switch controllers described in the port information  
table;

providing a device setup request for said target switch  
controller; and

updating a setup of said switch device associated with said  
target switch controller in response to said device setup  
request.

15-16. (canceled)